

SPECIFICATION SHEET

Power Ratings		kW	kVA
Power	Standby	80	125
	Prime	72	86
0.8 PF	240V	277	
Single output Voltage Change Selector Switch: 120/240V, 120/208V, 277/480V			

Rating Definitions: Rated for 1800 rpm.

Standby ratings is applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. A standby rated engine should be sized for a maximum of an 80% average load factor and 200 hours of operation per year. This includes less than 25 hours per year at the Standby Power rating. Ratings are established based on 85°F (29°C) and an elevation of 1,000 feet (305 meters). (Generator rated & tested in 40°C ambient)

STANDARD FEATURES:

Tradewinds Power Corp (TPC) fully integrated Mobile power generator set, provides optimum performance, reliability and versatility. Efficiency matched heavy duty diesel engine, with an AC Synchronous, brushless, single bearing alternator. All TPC systems and components are prototyped, assembled and tested within a purpose built packaging, manufacturing, and test facility.

Engine:

- DEUTZ model TCD 3.6 L4 series diesel engine.
- U.S. EPA non road (or off road) Tier 4 Final.
- Aftertreatment oxidation catalyst (DOC) and selective catalytic reduction (SCR).
- Electronic high pressure common rail.
- Heavy duty rated for standby and continuous prime power operation.
- Cooling system capable of operation at 120°F ambient.
- Series turbocharged aftercooled.
- DEUTZ Common Rail injection system and the electronic engine control (EMR 4) with intelligent link to the drive management ensure optimum engine performance at low fuel consumption.

Alternator:

- Marathon Electric 4-pole, brushless, 12 leads AC alternator
- Double shielded and pre-lubricated single bearing
- Class H insulation UL1446 utilizes an unsaturated polyester varnish for optimal insulation life and superior moisture protection. A tropical insulation is added for increased environmental protection
- Optimized electrical design with four-pole, brushless features, utilizes a 2/3 pitch winding to minimize harmonic distortion
- Vacuum-impregnated windings with fungus-resistant epoxy for dependability and long-life NEMA MG-32, BS5000, IEC 34-1.
- Permanent Magnet Generator (PMG) Excitation with BE2000 voltage regulator.

Starting System:

- 12-VDC Starter
- Engine mounted Battery Charging Alternator
- Battery Cables and Rack along with Grounding Strap


Factory Fitted Generator Options for Model TDE80:

- **Voltage selector switch:** Single output 120/240V, 120/208V, 277/480V
- **Weather Protective Enclosure:** constructed of Marine Grade Aluminum 0.125 thickness, SS Hardware, white powder coat paint finish on both sides, sound Insulation resistant to high temperatures, fuel and oil, hinged / removable / keyed alike doors, and 175mph wind load rating, and sound attenuation 68dBA measured at 27ft
- **Fuel Tank:** Double walled built to UL 142 specifications which include but not limited to: leak detection, low fuel level, mechanical fuel gauge, brass collar, lockable vented cap.
- **Trailer:** DOT road towing heavy duty steel or aluminum, electric or hydraulic brakes, 10,000lb. cap. 2 spring axle, 7-way RV style plug, adjustable channel 6-Hole 5-position Military Hitch (3" lunette eye) coupler, 15" high side wind jack, and semi-gloss textured urethane UV resistant waterproof paint coating for protection against rust, corrosion, salt and damp conditions. LED running lights along with DOT approved reflective red and white tape.
- **Battery Charge:** Fully automatic self adjusting to generator battery 6 Amp, 12 VDC, 90-265A AC 50/60Hz 115 VAC, compact type, UL Listed.

MOBILE DIESEL GENERATOR SET

FUEL: DIESEL

ENGINE: DEUTZ




Model Depicted: TDE80 T4
with Enclosure and DOT Trailer Options

CONNECTION PANEL & CONTROLS:

1. 800A rated CAM docking station 120/240V, 120/208V, 277/480V, female connectors with snap cover
2. 2 x (2 x Receptacle 120V-20A duplex GFCI)
3. 1 x Receptacle 30A 120V
4. 1 x Receptacle 30A 240V
5. 1 x Receptacle Twist Lock 50A 240V
6. Terminal connection panel lid

Note: DGC 2020 controller within enclosure, & emergency stop mounted externally



AUTOMATIC GENERATOR CONTROLLER DGC2020:

- Automatic generator controller with analog display of all functions
- Microprocessor Based, Navigation key with large LCD display
- SAE J1939 CANBUS Communication
- Event Recording
- Transfer Switch Control (main failures)
- Alternator Protection: under/over voltage, under/over frequency
- Engine Protection: Low oil pressure, High coolant temperature, Over speed & over crank, Sender Unit failure, Fuel Failure sensor, Battery Charger Failure
- All protections are programmable as Alarms or Pre-alarms
- Metering (ample range): Volts, Current, Hz, Watts, VA, Pf, Oil Pressure, Coolant Temperature, RPM, DC Volts, Fuel Level, Engine running time
- Engine Control with Timers
- External remote start input (on or off load)
- 16 programmable contact inputs - 7 Contact outputs

SCADA interface points:

- No fuel, Low fuel
- Low battery charging voltage
- Engine running
- Common engine alarm
- Switch in Emergency Position

Optional Equipment:

- Low coolant level switch
- 17-light remote annunciator panel
- Low coolant level switch


WARRANTY:

- Engine covered under the original equipment manufacturer's warranty - consult Tradewinds Power Corp for details
- Complete package supplied with 2-year limited warranty

The manufacture reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

ENGINE SPECIFICATION:	
Manufacturer and Model	DEUTZ Model TCD 3.6 L4
Emissions	EPA Tier 4
Engine speed (rpm)	1800
Max. (Cont.) HP Power 1800 rpm	135
Cylinder arrangement	4 In-line
Engine combustion system	Direct Injection
Aspiration	Turbo-charged aftercooled
Fuel direct injection system (Diesel)	High Pressure Common Rail
Number of Cylinders	4
Displacement in ³ (liters)	221 (3.6)
Bore and Stroke inches (mm)	3.9 x 4.7 (98 x 120)
Cooling	Water-cooled
Governor	Common Rail Electronic Control
Starting aids	Glow Plug
Compression ratio	TBA
Air cleaner type	Dry Type
Sound at 1m from engine block dBA	111.5
Max. Exh. Temp at full load degrees °F (°C)	883 (473)
Exhaust aftertreatment	DOC/DPF
COOLING SYSTEM FOR OPERATING AT 120°F AMBIENT:	
Cooling System	Water-cooled
Engine Coolant Capacity quarts (Liters)	4.8 (18.3)
Fan	Belt driven pusher fan
Radiator	Engine mounted
Eng. Cooling air flow - ft ³ /sec (m ³ /sec)	137.7 (3.9)
LUBRICATING SYSTEM:	
Total lubricating capacity quarts (Liter)	3.57 (13.5)
Recommended lubricating oil grade	SAE 10W-30
Oil Pressure – psi (kPA)	TBA
Oil Filter	Full flow spin on, cartridge type

ENGINE ELECTRICAL SYSTEM:	
Starting motor voltage	12 volt
Charging alternator output - Amps	100
Wet Cell Battery	Lead Acid
ALTERNATOR:	
Configuration	12-wire brushless rotating field
Frequency	60hz
Voltage regulation	PMG PM300
No load to full load voltage regulation	1/4% from no load to full load
Coupling	Flange to Flywheel Housing
Bearing	Single
Manufacturer	Marathon
Model	362PSL36115
Load acceptance	2/3 pitch design
Compliance	NEMA MG-1
TIF Factor	Shall not exceed 50
FUEL CONSUMPTION: PER HOUR GALS (LITERS) {STANDBY RATING}	
100%	8.7 (33.1)
75%	6.0 (22.6)
50%	4.2 (16.1)
25%	2.5 (9.3)
CONTROL PANEL SPECIFICATIONS:	
Manufacturer (Model)	Basler (DGC-2020ES)
MPC-10 Controller Inputs	16
MPC-10 Controller Outputs	12
Operating power/consumption	6-32 VDC; Average load 14.2W
Communications	UL 508 R & CSA C22.2 #14
GENERATOR OPTIONS:	
Enclosure	Aluminum sound attenuated to 68 dBA
Base arrangement	Rigid steel base frame with AVMS
Spill containment	UL double wall base mounted

DIMENSIONS & ARRANGEMENT DRAWING MOBILE MODEL (WITH DOT TRAILER & ENCLOSURE OPTION): TDE80 T4


KEY DIMENSIONS AND WEIGHT BASIC OPEN SET, SOUND ENCLOSURE AND MOUNTED ON DOT TRAILER (* = Option Equipment)										
Description (inches)	Height	Width		Length		Dry weight lbs	Wet Weight lbs	Sound dBA	Fuel Tank Gals *	
Enclosed Set	H2	62.0	W2	36.0	L2	103.0	2940	3015	68	250
Trailer mounted *	H3	103.34	W3	74.57	L3	203.97	6015	6158		